

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

68066 U.S. PTO  
08799073  
02/11/97

Applicants: Mark E. Davis, et al.  
Docket: ST996505  
Title: STREAMING COMPUTER SYSTEM AND METHOD WITH MULTI-VERSION PROTOCOL COMPATIBILITY

CERTIFICATE UNDER 37 CFR 1.10  
'Express Mail' mailing label number: EM372099365US  
Date of Deposit: February 11, 1997  
I hereby certify that this paper or fee is being deposited with the United States Postal Service 'Express Mail Post Office To Addressee' service under 37 CFR 1.10 and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.  
By: *Elayne Napoles*  
Name: Elayne Napoles

BOX PATENT APPLICATION  
Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

We are transmitting herewith the attached:

- ☒ Transmittal sheet, in duplicate, containing Certificate under 37 CFR 1.10.
- ☒ Utility Patent Application: Spec. 25 pgs; 30 claims; Abstract 1 pgs.  
The fee has been calculated as shown below in the 'Claims as Filed' table.
- ☒ 4 sheets of informal drawings
- ☒ Two signed Combined Declarations and Powers of Attorney
- ☒ Two Assignments of the invention to International Business Machines Corporation, Recordation Form Cover Sheet
- ☒ A check in the amount of \$1,310.00 to cover the Filing Fee
- ☒ A check for \$40.00 to cover the Assignment Recording Fee.
- ☒ Return postcard

CLAIMS AS FILED

Number of Claims Filed	In Excess of:	Number Extra	Rate	Fee
Basic Filing Fee				\$770.00
Total Claims				
30	20	10	22.00	= \$220.00
Independent Claims				
7	3	4	80.00	= \$320.00
MULTIPLE DEPENDENT CLAIM FEE				\$0.00
TOTAL FILING FEE				\$1310.00

Please charge any additional fees or credit overpayment to Deposit Account No. 13-2724. A duplicate of this sheet is enclosed.

MERCHANT, GOULD, SMITH, EDELL,  
WELTER & SCHMIDT  
Westwood Gateway II, Suite 400  
11150 Santa Monica Blvd.  
Los Angeles, CA 90025  
(310) 445-1140

By: *George H. Gates*  
Name: George H. Gates  
Reg. No.: 33,500  
Initials: GHG/en



4

1310-101

A

STREAMING COMPUTER SYSTEM AND METHOD WITH  
MULTI-VERSION PROTOCOL COMPATIBILITY

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The invention is generally related to the storage and retrieval of data from streams, and in particular, to a manner of supporting multiple versions of a streaming protocol.

10

2. Description of Related Art

Streaming provides a mechanism for the storage and retrieval of persistent data in a computer system, or for the transmission of data between computer system modules, whether or not they are within the same computer system. With streaming, data is embedded in data streams that follow a predetermined streaming protocol to enable a module that receives a data stream to reliably decode and retrieve the data therefrom.

20

Many streaming protocols are designed to support the transmission of information between modules irrespective of their underlying hardware and/or software platforms. This is a particular concern with distributed and open computer systems, where computing tasks may be broken up and handled

25

on multiple computers or multiple applications within a

25120 82066280

computer by passing objects between the computers or applications. With distributed systems, e.g., OMG's Common Object Request Broker Architecture (CORBA), IBM's Distributed System Object Component (DSOM), etc., often the  
5 underlying platforms may vary, and a module may not be able to direct data to a particular computer, or if it can, may not be able to detect the underlying platform of the receiving computer. Likewise, a module that formats an object for transmission to or use by another module in a  
10 separate application or computer may not be able to detect the particular application which will ultimately utilize the object, e.g., as with IBM's OpenDoc, Microsoft's Object Linking and Embedding (OLE), etc.

One concern that is raised with respect to such  
15 streaming protocols is that of release-to-release data compatibility. In particular, as computer systems and applications are upgraded, streaming protocols may likewise be upgraded to support enhanced functionality. The upgraded computer systems and applications, however, may still be  
20 required to communicate with computer systems and applications that only support earlier releases, or versions, of a streaming protocol. Likewise, the earlier versions may be required to communicate with computer systems and applications that support the newer versions.  
25 Since it is often difficult, if not impossible, to detect

supported versions of a streaming protocol, some incompatibilities may occur.

Such incompatibilities may be eliminated by upgrading all computers and applications in a computer system to  
5 support the same streaming protocol, but this is often not feasible due to cost or control issues.

Therefore, a significant need exists for a manner of ensuring release-to-release data compatibility of streaming protocols within a computer system.

10

#### SUMMARY OF THE INVENTION

The invention addresses these and other problems associated with the prior art in providing a streaming protocol whereby subsequent versions of a protocol are  
15 purely additive relative to earlier versions. When a data segment is transmitted as a data stream, a first stream of data that is in accordance with a first version of the protocol is transmitted, with additional streams of data that are in accordance with subsequent versions of the  
20 protocol appended in sequence to the first stream of data. A write module that transmits the data stream appends all such streams of data up to and including the stream of data that is in accordance with the version of the streaming protocol implemented by the write module.

0379903-0449  
25720-206280

At the receiving end, a read module receives the first stream of data, as well as each additional stream of data up to and including that which is in accordance with the version of the protocol that is implemented by the read module. If the end of the data segment is detected prior to receiving all of the data expected by the read module (indicating that the version of the write module was earlier than that of the read module), the read module will detect this and handle the prior version of the data segment accordingly. Moreover, if the end of the data segment is not detected after receiving all of the data expected by the read module (indicating that the version of the write module was later than that of the read module), any remaining data in the data segment is disregarded. Consequently, forward and backward compatibility between streaming protocol versions are concurrently supported.

These and other features, which characterize the invention, are set forth in the claims annexed hereto and forming a further part hereof. However, for a better understanding of the invention, and of the various advantages and objectives attained by its use, reference should be made to the Drawing, and to the accompanying descriptive matter, in which there is described illustrated embodiments of the invention.

## BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the Drawings in which like reference numbers represent corresponding parts throughout:

FIG. 1 is a block diagram of an exemplary hardware environment for use with the illustrated embodiments of the invention;

FIG. 2 is a block diagram illustrating the transmission of a data stream between write and read modules consistent with the principles of the present invention;

FIG. 3 is a flowchart of a WriteToStream routine consistent with the principles of the invention;

FIG. 4 is a flowchart of a ReadFromStream routine consistent with the principles of the invention;

FIG. 5 is a block diagram of an exemplary data stream consistent with the invention; and

FIG. 6 is a block diagram of another exemplary data stream consistent with the invention.

## DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

In the following description, reference is made to the accompanying drawings which form a part hereof, and which is shown by way of illustration, embodiments of the invention. It is understood that other embodiments may be utilized and structural changes may be made without departing from the scope of the present invention.

## Hardware Environment

FIG. 1 is an exemplary hardware environment used to implement an illustrated embodiment of the invention. The present invention is typically implemented in a computer system 5 which may include one or more computers 10, e.g., in a stand-alone environment, or, as shown in FIG. 1, in a connected network 8. For example, it is over network 8 that data streams may be passed between each computer 10. Network 8 may be, for example, a LAN, a WAN, or a public network such as the Internet.

It is envisioned that attached to each of computers 10 may be a monitor 14 (e.g., a CRT, an LCD display or other display device); and non-volatile storage 16 (e.g., hard, floppy, and/or CD-ROM disk drives). Also included may be various input devices, for example, a keyboard 12.

Generally, the computer programs (illustrated at 20) which implement the illustrated embodiments of the invention are tangibly embodied in a computer-readable medium, e.g., one or more of the fixed and/or removable data storage data devices 16. Under control of computer 10, the computer programs may be loaded from the data storage devices 16 into the memory of computer 10. The computer programs comprise instructions which, when read and executed by computer 10, cause computer 10 to perform the steps necessary to execute the steps or elements of the present invention.

Those skilled in the art will recognize that the exemplary environment illustrated in FIG. 1 is not intended to limit the present invention. Indeed, those skilled in the art will recognize that other alternative hardware  
5 environments may be used without departing from the scope of the present invention.

#### Software Implementation

The illustrated embodiments of the invention generally  
10 provide release-to-release data compatibility over multiple versions of a streaming protocol by requiring version modifications to the streaming protocol to be purely additive, so that a data stream output in accordance with a streaming protocol includes data segments sequenced  
15 according to each version of the streaming protocol up to and including the version implemented in the write module outputting the data stream. A read module which receives the data stream includes forward compatibility by disregarding any data related to later versions after all of  
20 the data up to and including the version of the module has been received. Backward compatibility is provided by detecting premature end tags and handling the unreceived data accordingly.

As shown in FIG. 2, illustrated embodiments of the  
25 invention are generally implemented in write modules, such



as write module 22, which output a data stream, and read modules, such as read module 24, which receive the data stream. It should be appreciated that the read and write modules may be software objects or components having one or more methods or routines that implement the functionality of the modules, and that the modules may be resident on the same computer, e.g., in different computer programs or applications that may communicate via streaming (as in OpenDoc and OLE). Moreover, the read and write modules may be resident on different computers within a networked computer system (e.g., in a distributed computer system such as DSOM or CORBA). Furthermore, the read and write modules need not be implemented on the same hardware and/or software platform (e.g., where a write module is implemented on a UNIX platform and a read module is implemented on a PC platform).

Data streams consistent with the invention are typically tag-delimited and may include data segments which represent objects and/or primitive data types. In addition, aliasing may be supported, whereby special information is written to the data stream to enable reconstruction of aliased pointers in the event that multiple pointers refer to the same data.

The data streams may be more or less serial, where all of the information required to reconstruct an object from a

data segment is stored within the data segment.

Consequently, no additional information, e.g., a separate database, need be streamed out at the end of a data stream as is required with some conventional streaming methods.

- 5 Moreover, the data streams need not be random access streams, although random access streams may also be supported.

The data streams are output by write modules in formats that are dictated by a streaming protocol which may be  
10 revised from time to time, thereby forming a plurality of versions of the streaming protocol. Consistent with the invention, revisions to the streaming protocol are purely additive, and are appended to one another in sequence. For example, FIG. 2 illustrates a data stream having a data  
15 segment 26 which includes, in sequence, streams of data according to versions 1 to  $n$  of a streaming protocol.

A write module may be considered to implement a particular version of a streaming protocol when the write module outputs data in the format dictated by that version  
20 of the streaming protocol. Likewise, data streams are received by read modules which expect the data to be formatted according to particular versions of a streaming protocol. A read module may therefore be considered to implement a particular version of a streaming protocol when

the read module expects to receive data in the format dictated by that version of the streaming protocol.

FIG. 3 illustrates a WriteToStream routine 50 for execution by a write module to stream out a data segment (here, a particular object) comprising a sequence of streams of data. For illustrative purposes, routine 50 may be considered to implement a version  $n$  of a streaming protocol. A corresponding ReadFromStream routine 100, which implements a version  $m$  of the streaming protocol is shown separately in FIG. 4. Routine 50 supports object aliasing, whereby subsequent references to objects that have been written to a stream may be replaced by alias tags, rather than writing additional copies of the object to the stream. However, it should be appreciated that support for aliasing may be omitted in some applications.

Routine 50 outputs a tag-delimited data stream whereby object data is preceded by a begin tag and followed by an end tag. In addition, alias tags are also used to point to the location of information in the data stream that is being aliased. Each tag may include an identifier field for identifying the type of tag, e.g., begin tag, end tag, object type tag, object alias tag, object type alias tag, etc. Each tag may also include a pointer field that points to another location in the data stream. Other tag formats may be used in the alternative.

007903 02449  
264420 24066280

Routine 50 begins in block 52 by determining whether an object type for the object, *typeinfo*, is stored in the current context. *Typeinfo* provides an object type for the object so that the object may be allocated and initialized (e.g., by calling an appropriate default constructor) to recreate the object. The current context is an object that maintains a record of the objects and object types therefor that have been written to a data stream. Each entry in the current context preferably includes an object type for the object, as well as a pointer to the location of the data in the data stream. It should be appreciated that the current context may be initialized in a separate routine, or in the alternative, routine 50 may initialize the current context if the routine determines that this has not been so done.

If the object type is not in the current context, the object type is saved in the current context in block 54, then the object type tag is written to the stream. If, on the other hand, the object type is in the current context, an alias tag is written to the stream in block 58. The pointer for the alias tag includes the byte offset in the data stream to the object type being referenced by the alias tag.

Next, in block 60, routine 50 determines whether the object itself is in the current context. If it is, then an alias tag, which points back to the first instance of the

00799073 004492  
261120 2056280

object in the data stream, may be written to the stream in  
block 62, whereby no further processing is required. The  
alias tag may be configured similar to the alias tag for the  
object type, with the pointer for the alias tag including  
5 the byte offset in the data stream to the object data being  
referenced thereby.

If, on the other hand, the object is not stored in the  
current context, the object is saved in the current context  
in block 64. Next, in block 64, a begin tag is written to  
10 the stream to delimit the start of the data for the object.  
The pointer for the begin tag may include, for example, the  
byte offset in the data stream to the matching end tag for  
the object.

Next, in block 68, all of the data for the object in  
15 accordance with the earliest (first) version of the  
streaming protocol is written to the stream in block 68.  
Any additional data for the object that is supported by  
subsequent versions of the streaming protocol up to and  
including the version *n* being implemented by routine 50 is  
20 thereafter appended to this data, as shown by blocks 70-72.  
Data for each version may be appended sequentially in order  
from earliest to latest version, with the current version  
implemented by the routine coming last in the data stream.

Each separate piece of data, for example, primitive  
25 fields, does not require tagging. Only version tags are

0279903 02149  
26120 2205220

required. This provides significant savings in stream storage as well as higher read performance. Moreover, information to support polymorphic streaming only need be emitted when necessary. The source write operation may  
5 determine the type of the object and compare it to the type of pointer. Information necessary to support a polymorphic read operation need only be stored in the stream if the type of object and the type of pointer are different. This represents very substantial savings in storage, write  
10 performance and especially read performance.

Once all of the data for the object is written to the data stream, the end tag, which matches the begin tag written in block 66, is written to the data stream in block 74. The pointer for the end tag generally includes the byte  
15 offset to the next tag in the data stream. After the end tag is written to the data stream, streaming of the object is complete.

It should be appreciated that routine 50 as shown in FIG. 3 is merely a template for streaming out a generic  
20 object, and thus may be provided in a framework or class library and modified by a programmer to tailor the routine depending upon the particular data structure of an object to be streamed out. Typically, blocks 68-72 of routine 50 are customized to stream out suitable object data for a specific  
25 object to the data stream. In practice, the object data may

vary greatly depending upon the particular object being written, as well as the version of the streaming protocol being used to stream out the object.

FIG. 4 illustrates a corresponding ReadFromStream routine 100 for execution by a read module to read in the data segment (here, an object) written to the data stream by routine 50. For illustrative purposes, routine 100 may be considered to implement a version *m* of a streaming protocol.

Routine 100 begins at block 102 by reading the object type *typeinfo* from the data stream. Next, it is determined whether the object type is an alias tag in block 104. If it is, control passes to block 106 to retrieve the object type from the current context. If it is not, control passes to block 108 to save the object type in the current context. As with routine 50, it may also be necessary to initialize the current context if not previously so done.

In either event, control next passes to block 110 to read the next tag from the data stream. Next, it is determined in block 112 whether this tag is an alias tag. If it is, then control passes to block 116 to retrieve from the current context the pointer to the previously-created object referenced by the alias tag, whereby retrieval of the object is then complete.

Otherwise, control passes to block 114 to allocate and initialize the object by calling the default constructor for

0079903-0449  
267120-205280

the object based upon its object type received from either the data stream or the current context. As noted above, the default constructor is the program code that forms a template for how to build an object from the forthcoming data in the data stream. It is the default constructor which typically defines what version of a streaming protocol is supported, since the default constructor expects to receive object data in a predetermined format. Other manners of allocating and initializing the object may be used in the alternative.

Next, control passes to block 118 to read the object data according to the first version of the streaming protocol from the data stream. At this time, the data is also used to build the object based upon the template provided by the default constructor.

Next, in block 120, it is determined whether the end of the object has been detected, typically by checking if an end tag is received when it is not expected. If so, this indicates that an earlier version of the streaming protocol was used to stream out the object data (i.e.,  $n < m$ ). In this case, control passes to block 122 to initialize (e.g., set to null or another default value) all of the object data according to each subsequent version of the streaming protocol (up to and including the version  $m$  implemented by routine 100). It may also be necessary to include suitable



program code in any other routines that handle the object to detect and specially handle the default values. Upon completion of initializing the object data, control passes to block 134 to save the object in the current context, 5 whereby streaming in of the object is complete.

Returning to block 120, if the end of the object is not detected, blocks 124-130, which are similar in operation to blocks 118-122, read in the object data according to the subsequent versions of the streaming protocol up to version 10 *m* implemented by routine 100. Also, between reading in the object data according to each subsequent, premature ends of blocks are detected in order to maintain backward compatibility and initialize any object data not supplied in the data stream.

15 Forward compatibility is provided by block 132, which skips to the end tag for the object in the data stream if the end tag has not yet been reached after reading in the object data according to version *m* of the streaming protocol (which typically occurs when  $n > m$ ). Thus, any object data 20 supplied for later versions of the streaming protocol is disregarded in building the object. However, any skipped data may be stored in the current context for later retrieval, e.g., as required for aliasing. Control then passes to block 134 to save the object in the current 25 context, whereby streaming in of the object is complete.





```

class Apple {
public:
    ...
    virtual void writeToStream(IDataStream& toWhere) const;
    virtual void readFromStream(IDataStream& fromWhere);
    ...
private:
    Orange *fOrange;
    Banana *fBanana;
    Banana *fExtBanana;
};

void Apple::writeToStream(IDataStream& toWhere) const {
    IStreamOutFrame    myStreamOutFrame;
    fOrange->writeToStream(toWhere);
    fBanana->writeToStream(toWhere);
    fExtBanana->writeToStream(toWhere);
}

void Apple::readFromStream(IDataStream& fromWhere) {
    IStreamInFrame    myStreamInFrame;
    fOrange->readFromStream(fromWhere);
    fBanana->readFromStream(fromWhere);
    if (!myStreamInFrame.atEnd())
        fExtBanana->readFromStream(fromWhere);
    else
        fExtBanana = NULL;
}

```

Table II: Second Version of Streaming Protocol

The writeToStream method for each version of the *Apple* class generally represents the object data writing steps 68-72 of routine 50. Similarly, the readFromStream method for each version of the *Apple* class generally represents the object data reading steps 118-130 of routine 100.

Backward compatibility may be illustrated by streaming out a first version of *Apple* and streaming in the second version of *Apple*. Suitable code for streaming out *Apple* is illustrated below in Table III below:

```
IDataStream*      myDataStream = ...
Apple*            myApple = new Apple();
...
myApple->writeToStream(*myDataStream);
```

*Table III: Stream Out Code - Backward Compatibility*

The format of the data stream generated by the above code is illustrated by data stream 40 in FIG. 5, whereby pointers from each tag are represented by arrows pointing to the targets of the pointers. It is assumed that none of *Apple*, *Orange*, and *Banana* have previously been output to the data stream, and thus, no aliasing is utilized when outputting the object data for *Apple*. As discussed above in

relation to routine 50 of FIG. 3, when no aliasing occurs, the general output to a data stream includes an object type tag, a begin tag, the object data, and an end tag.

Referring to the first version of the *Apple* class in Table I, the object data for the first version of *Apple* includes *Orange* and *Banana*, and thus the two *WriteToStream* calls made in the *WriteToStream* method in the *Apple* class correspond generally to block 68 of routine 50 (FIG. 3). Moreover, since this is the first version of the *Apple* class, blocks 70-72 are omitted. Each of *Orange* and *Banana* also output data in the same general manner as routine 50, and thus the object data portion of the data stream for *Apple* includes an object type tag, a begin tag, object data, and an end tag for both *Orange* and *Banana*.

Streaming in of the data stream of FIG. 5 follows the general program flow of routine 100 of FIG. 4. Here, the statements in the *readFromStream* method of Table II correspond generally to blocks 118-124 of routine 100, with blocks 126-130 omitted since this is the second version of the *Apple* class. Here, since the *readFromStream* method for the second version of the *Apple* class receives the end tag for *Apple* prior to receiving any *fExtBanana* object, this object is initialized to null.

Forward compatibility may be illustrated by streaming out a second version of *Apple* and streaming in the first version of *Apple*. Suitable code for streaming out the second version of *Apple* is illustrated below in Table IV below. Moreover, to illustrate aliasing, the streaming out of an additional instance of *Banana* is performed following *Apple*.

10	<pre>IDataStream*      myDataStream = ... Apple*            myApple = new Apple(); Banana*           myBanana = new Banana(); myBanana = myApple.fExtBanana; ... myApple-&gt;writeToStream(*myDataStream); myBanana-&gt;writeToStream(*myDataStream);</pre>
Table IV: Stream Out Code - Forward Compatibility	

The format of the data stream generated by the above code is illustrated by data stream 45 in FIG. 6, with pointers from each tag represented by arrows pointing to the targets of the pointers. Referring to the second version of the *Apple* class in Table I, the object data for the first version of *Apple* includes *Orange* and *Banana*, and thus the

first two WriteToStream calls made in the WriteToStream method in the *Apple* class correspond generally to block 68 of routine 50 (FIG. 3). The data according to the second version of the streaming protocol, *fExtBanana*, is streamed out after *Orange* and *Banana*, and thus, the last WriteToStream call made in the WriteToStream method in the *Apple* class corresponds generally to block 70 of routine 50.

Also, as may be seen from the data stream of FIG. 6, when *fExtBanana* is streamed out, the object type therefor is already stored in the current context as a result of streaming out *fBanana*. Consequently, an alias tag for the *fExtBanana* object type is streamed out instead the object type itself.

As an illustration of aliasing, after *Apple* is streamed out, *myBanana* is streamed out. Since both the object type and the object itself have been streamed out with *Apple*, both are stored in the current context. Thus, when *myBanana* is streamed out, alias tags for the object type and the object are output to the data stream in lieu of the actual object data.

Streaming in of the data stream of FIG. 6 also follows the general program flow of routine 100 of FIG. 4. Here, the statements in the readFromStream method of Table I correspond generally to block 118 of routine 100, with



0079003-024497  
267720 E2066280

blocks 120-130 omitted since this is the first version of the *Apple* class. When the object data for *Apple* is read in, only *Orange* and *Banana* (the data according to the first version of *Apple*) are read in. The `readFromStream` method

5 terminates, and the remaining object data in *Apple* is disregarded (see block 132 of FIG. 4). This is implemented in the *Apple* class by virtue of *IStreamInFrame* being a scoped object whose scope ends after *Banana* is streamed in. A destructor method (not shown) is called when the scope of  
10 *IStreamInFrame* ends to skip to the end of *Apple*.

Consequently, for data stream 45, the object data between the *Banana* end tag and the *Apple* end tag may be disregarded and skipped, thereby providing forward compatibility for the *Apple* class. This data may, however, be stored in the  
15 current context for retrieval by aliased objects.

For streaming in the aliased *myBanana* after streaming in *Apple*, the alias tags for the *Banana* object type and the *Banana* object itself are read, and then the object type and object data are read out from the current context (i.e., as  
20 shown by blocks 108 and 116 of routine 100 in FIG. 4). Streaming in of data stream 45 is then complete.

Various modifications may be made to the illustrated embodiments without departing from the spirit and scope of the invention. For example, other actions may be taken than



WHAT IS CLAIMED IS:

1. A method of transmitting a data segment in a data stream using a write module of the type which implements a selected one of a plurality of versions of a streaming  
5 protocol, the method comprising the steps of:

(a) outputting a first stream of data according to a first version of the streaming protocol; and

(b) sequentially appending additional streams of data to the first stream of data according to each subsequent  
10 version of the streaming protocol up to and including the selected version, if the selected version of the streaming protocol is not the first version of the streaming protocol.

2. The method of claim 1, further comprising the step  
15 of receiving the data segment from a data stream using a read module of the type which implements a second selected one of the plurality of versions of the streaming protocol, the receiving step including the steps of:

receiving the first stream of data;

20 if the second selected version is earlier than the first selected version, receiving each additional stream of data according to each subsequent version of the streaming protocol up to and including the second selected version, and disregarding any remaining data in the data segment;

if the second selected version is equal to or later  
than the first selected version, sequentially receiving the  
additional streams of data according to each subsequent  
version of the streaming protocol up to and including the  
5 second selected version; and

testing, prior to receiving each additional stream of  
data, whether an end of the data segment has been detected,  
and if so, terminating reception of the data segment prior  
to receiving the additional stream of data according to the  
10 second selected version.

3. The method of claim 2, wherein the data segment is  
an object.

15 4. The method of claim 3, wherein the data segment  
includes all of the data necessary to reconstruct the  
object; wherein the data stream is serial.

5. The method of claim 3, wherein the testing step  
20 includes the step of initializing object data that is not  
received from the data stream to a default value.

6. The method of claim 3, further comprising the  
steps of:

25 transmitting an object type for the data segment; and

receiving the object type, including the steps of allocating and initializing an object when receiving the data segment based upon the object type.

5           7.    The method of claim 2, wherein the read and write modules are resident on the same computer.

8.    The method of claim 2, wherein the read and write modules are resident on separate computers.

10

9.    The method of claim 1, further comprising the step of delimiting the data segment in the data stream using begin and end tags.

15           10.   The method of claim 9, wherein no additional tags are embedded in the data segment between the begin and end tags.

20           11.   The method of claim 1, further comprising the steps of:

          determining whether the data segment is stored in a current context for the data stream;

          if so, transmitting an alias tag in lieu of the data segment; and

if not, storing the data segment in the current context.

12. The method of claim 1, wherein the data stream is  
5 a non-random access data stream.

13. A method of receiving a data segment from a data stream using a read module of the type which implements a selected one of a plurality of versions of a streaming  
10 protocol, the method comprising the steps of:

(a) receiving a first stream of data according to a first version of the streaming protocol;

(b) if the selected version of the streaming protocol is not the first version of the streaming protocol,  
15 sequentially receiving additional streams of data according to each subsequent version of the streaming protocol up to and including the selected version; and

(c) testing, prior to receiving each additional stream of data, whether an end of the data segment has been  
20 detected, and if so, terminating reception of the data segment prior to receiving the additional stream of data according to the selected version.

14. The method of claim 13, further comprising the  
25 step of disregarding any remaining data in the data segment,

if the end of the data segment has not been detected upon receiving the additional stream of data according to the selected version.

5        15. The method of claim 14, further comprising the step of storing the data segment in a current context, including any disregarded data therefrom.

10        16. The method of claim 13, wherein the data segment is an object.

15        17. The method of claim 16, wherein the testing step includes the step of initializing object data that is not received from the data stream to a default value.

18. The method of claim 16, further comprising the steps of:

receiving an object type for the data segment; and

20        allocating and initializing an object based upon the object type to build the object from the streams of data in the data segment.

25        19. A computer system that transmits data segment in a data stream, the computer system comprising a write module that implements a selected one of a plurality of versions of

a streaming protocol, and that outputs the data segment in the data stream, wherein the write module comprises:

(a) means for outputting a first stream of data according to a first version of the streaming protocol; and

5 (b) means for sequentially appending additional streams of data to the first stream of data according to each subsequent version of the streaming protocol up to and including the selected version, if the selected version of the streaming protocol is not the first version of the  
10 streaming protocol.

20. The computer system of claim 19, wherein the data segment is an object.

15 21. The computer system of claim 19, wherein the write module further comprises means for transmitting an object type for the data segment.

22. The computer system of claim 19, wherein the write  
20 module further comprises means for transmitting begin and end tags to delimit the data segment in the data stream.

23. The computer system of claim 19, wherein the write module further comprises means for transmitting an alias tag



in lieu of the data segment if the data segment is stored in a current context for the data stream.

24. A computer system that receives a data segment  
5 from a data stream, the computer system comprising a read module that implements a selected one of a plurality of versions of a streaming protocol, and that receives the data segment from the data stream, wherein the read module comprises:

10 (a) means for receiving a first stream of data according to a first version of the streaming protocol;

(b) means for sequentially receiving additional streams of data according to each subsequent version of the streaming protocol up to and including the selected version,  
15 if the selected version of the streaming protocol is not the first version of the streaming protocol; and

(c) means for testing whether an end of the data segment has been detected, and if so, for terminating reception of the data segment prior to receiving the  
20 additional stream of data according to the selected version prior to receiving each additional stream of data.

25 25. The computer system of claim 24, wherein the read module comprises means for disregarding any remaining data in the data segment, if the end of the data segment has not

been detected upon receiving the additional stream of data according to the selected version.

26. The computer system of claim 24, wherein the data  
5 segment is an object.

27. The computer system of claim 26, wherein the read  
module comprises means for receiving an object type for the  
data segment, and for allocating and initializing an object  
10 based upon the object type to build the object from the  
streams of data in the data segment.

28. A computer system comprising first and second  
computers that transmit a data segment in a data stream from  
15 the first computer to the second computer, the first  
computer comprising means for implementing a first selected  
one of a plurality of versions of a streaming protocol, and  
the second computer comprising means for implementing a  
second selected one of the plurality of versions of the  
20 streaming protocol, wherein:

(a) the first computer includes a write module for  
transmitting the data segment, wherein the write module  
outputs a first stream of data according to a first version  
of the streaming protocol, and if the first selected version  
25 is not the first version of the streaming protocol, the

write module sequentially appends to the first stream of data additional streams of data according to each subsequent version of the streaming protocol up to and including the first selected version; and

5 (b) the second computer includes a read module for receiving the data segment from the first computer, wherein the read module receives the first stream of data, wherein if the second selected version is earlier than the first selected version, the read module receives each additional stream of data according to each subsequent version of the streaming protocol up to and including the second selected version, and disregards any remaining data in the data segment, wherein if the second selected version is equal to or later than the first selected version, the read module  
10 sequentially receives the additional streams of data according to each subsequent version of the streaming protocol up to and including the second selected version, and wherein, prior to receiving each additional stream of data, the read module detects whether an end of the data  
15 segment has been detected, and if so, terminates reception of the data segment prior to receiving the additional stream of data according to the second selected version.  
20

29. A program storage device, readable by a computer  
25 system and tangibly embodying one or more programs of

instructions executable by the computer system to perform method steps of transmitting a data segment in a data stream in a format based upon a selected one of a plurality of versions of a streaming protocol, the method comprising the

5 steps of:

(a) outputting a first stream of data according to a first version of the streaming protocol; and

(b) sequentially appending additional streams of data to the first stream of data according to each subsequent

10 version of the streaming protocol up to and including the selected version, if the selected version of the streaming protocol is not the first version of the streaming protocol.

30. A program storage device, readable by a computer

15 system and tangibly embodying one or more programs of instructions executable by the computer system to perform method steps of receiving a data segment from a data stream according to a selected one of a plurality of versions of a streaming protocol, the method comprising the steps of:

20 (a) receiving a first stream of data according to a first version of the streaming protocol;

(b) sequentially receiving additional streams of data according to each subsequent version of the streaming protocol up to and including the selected version, if the





# ABSTRACT OF THE DISCLOSURE

A forward and backward compatible streaming protocol requires subsequent versions of the protocol to be purely additive relative to earlier versions. When a data segment is transmitted as a data stream, a first stream of data that is in accordance with a first version of the protocol is transmitted, with additional streams of data that are in accordance with subsequent versions of the protocol appended in sequence to the first stream of data. When a read module implements an earlier version of the protocol than a write module, the data segment is truncated to include only the data supported by the version implemented by the read module. On the other hand, when the read module implements a later version of the protocol than the write module, receipt of the data segment is terminated after the data supported by the version implemented by the write module is received.

"Express Mail" mailing label number: EM37209936SUS  
Date of Deposit: FEBRUARY 11, 1997  
I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231.

CLAYNE NAPOLES  
(printed name)

Clayne Napoles  
(signature)











Fig. 4






Fig. 6

## DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

DOCUMENT: ST996505

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

STREAMING COMPUTER SYSTEM AND METHOD WITH MULTI-VERSION PROTOCOL COMPATIBILITY

the specification of which (check one)

X is attached hereto.  
 was filed on \_\_\_\_\_  
 as Application Serial No. \_\_\_\_\_  
 and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)			Priority Claimed	
None			Yes	No
(Number)	(Country)	(Day/Month/Year Filed)		

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56, which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

None			
(Application Serial No.)	(Filing Date)	(Status)	(patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

261120 3 2005 280

## DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

DOCKET: ST996305

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Marilyn Smith Dawkins, Registration No. 31,140, Christopher A. Hughes, Registration No. 26,914, David J. Kappos, Registration No. 34,357, John E. Hoel, Registration No. 26,279, Prentiss W. Johnson, Registration No. 33,123, Edward A. Pennington, Registration No. 32,588, Joseph C. Redmond, Jr., Registration No. 18,753, all of whom are attorneys with IBM Corporation; and

George H. Gates, Registration No. 33,500, Gregory B. Wood, Registration No. 28,133, Raymond A. Bogucki, Registration No. 17,426, and Charles Berman, Registration No. 29,219, all of whom are attorneys with the law firm of Merchant, Gould, Smith, Edell, Walter & Schmidt

Send correspondence to: George H. Gates, Esq.  
Merchant, Gould, Smith, Edell,  
Walter & Schmidt  
Suite 400  
11150 Santa Monica Boulevard  
Los Angeles, California 90025-3395

Direct Telephone Calls to: (name and telephone number) George H. Gates, (310) 445-1140

Full name of sole or first joint-inventor: <sup>1-00</sup> Mark E. Davis

Inventor's signature: Mark E. Davis Date: 2-6-97

Residence: 2509 Alpine Road, Menlo Park, California 94025 CA

Citizenship: U.S.A.

Post Office Address: Same

Full name of second joint-inventor: Andrew G. Heninger

Inventor's signature: Andrew G. Heninger Date: 2-6-97

Residence: 1511 Corte Via, Los Altos, California 94024

Citizenship: U.S.A.

Post Office Address: Same

251120-22055280

## DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

DOC#: ST996505

Full name of third joint-inventor: Marc (NMI) Jablonski

Inventor's signature:

Date:

Residence: 332 Waverley Street, Palo Alto, California 94301

Citizenship: U.S.A.

Post Office Address: Same

Full name of fourth joint-inventor: <sup>4-00</sup> Glenn A. Marcy

Inventor's signature:

Date:

Residence: 2260 Homestead Ct. #308, Los Altos, California 94024

Citizenship: U.S.A.

Post Office Address: Same

Full name of fifth joint-inventor: Michael C. Werts

Inventor's signature:

Date:

Residence: 2674 Calico Court, Morgan Hill, California 95037

Citizenship: U.S.A.

Post Office Address: Same

2025-02-06 19:26

## DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

DOCKET: ST996505

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

STREAMING COMPUTER SYSTEM AND METHOD WITH MULTI-VERSION PROTOCOL COMPATIBILITY

the specification of which (check one)

X is attached hereto.  
 \_\_\_\_\_ was filed on \_\_\_\_\_  
 \_\_\_\_\_ as Application Serial No. \_\_\_\_\_  
 and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

None  
(Number)

(Country)

(Day/Month/Year Filed)

\_\_\_\_ Yes \_\_\_\_ No

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56, which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

None  
 (Application Serial No.) (Filing Date) (Status) (patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

## DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

DOCKET: ST996505

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Marilyn Smith Dawkins, Registration No. 31,140, Christopher A. Hughes, Registration No. 26,914, David J. Karpog, Registration No. 34,357, John E. Hoel, Registration No. 26,279, Prentiss W. Johnson, Registration No. 33,123, Edward A. Pennington, Registration No. 32,588, Joseph C. Redmond, Jr., Registration No. 18,753, all of whom are attorneys with IBM Corporation; and

George H. Gates, Registration No. 33,500, Gregory B. Wood, Registration No. 28,123, Raymond A. Borucki, Registration No. 17,426, and Charles Berman, Registration No. 29,249, all of whom are attorneys with the law firm of Merchant, Gould, Smith, Edell, Welter & Schmidt

Send correspondence to: George H. Gates, Esq.  
Merchant, Gould, Smith, Edell,  
Welter & Schmidt  
Suite 400  
11150 Santa Monica Boulevard  
Los Angeles, California 90025-3395

Direct Telephone Calls to: (name and telephone number) George H. Gates, (310) 445-1140

Full name of sole or first joint-inventor: Mark E. Davis

Inventor's signature:

Date:

Residence: 2509 Alpine Road, Menlo Park, California 94025

Citizenship: U.S.A.

Post Office Address: Same

Full name of second joint-inventor: Andrew G. Heninger

Inventor's signature:

Date:

Residence: 1611 Corte Via, Los Altos, California 94024

Citizenship: U.S.A.

Post Office Address: Same

## DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

DOCKET: ST996505

2-00  
Full name of third joint-inventor: Marc (NMI) Jablonski

Inventor's signature:



Date:

FEBRUARY 5, 1987

Residence: 332 Waverley Street, Palo Alto, California 94301 <sup>LR</sup>

Citizenship: U.S.A.

Post Office Address: Same

Full name of fourth joint-inventor: Glenn A. Marcy

Inventor's signature:

Date:

Residence: 2260 Homestead Ct. #208, Los Altos, California 94024

Citizenship: U.S.A.

Post Office Address: Same

Full name of fifth joint-inventor: Michael C. Werts

Inventor's signature:

Date:

Residence: 2674 Calico Court, Morgan Hill, California 95037

Citizenship: U.S.A.

Post Office Address: Same